

200W – 3200K

Canara Fresnel equipped with an enhanced COB LED source providing a higher output with a significant efficiency, this 200 mm Fresnel lens presents an exceptional flat and variable beam angle with very wide opening, combined with an electronic flicker-free dimmable power supply unit to create a powerful yet economical LED wash & Spotlight make it the perfect choice for theatre, Auditoriums, TV studio, Production House, event and architectural applications.



MODEL : CAN LED-T1

TECHNICAL SPECIFICATIONS

LIGHT SOURCE


- Lamp : 200W COB LED
- Color temperature (CCT) : 3200K
- CRI : > 95, TLCI: > 95, R9 Value: > 92
- Color Quality Scale (CQS) : > 95
- Lamp life : L70 >50000 Hours @ 55°C

ELECTRICAL

- Flicker free universal auto-ranging electronic switch mode power supply 100~240 VAC Nominal, 50/60 Hz
- 0 to 100% 8 Bit Linear Dimming
- Power Factor ≥ 0.95 @ 230V 50Hz
- Max mains current drawn 0.46A @ 230V AC 50Hz
- Max LED current drawn 3.70A @ 54V DC
- Power supply cable: 3 meter 3 Core 1Sq mm FRLS grade PVC cable with IEC Plug

SPECIAL FEATURES

- Delivers the output performance of its 1000W Incandescent complement at 200W.
- Double accessories slot for inserting color filters, barndoor and other accessories with lock retaining clip.
- Fully RDM Compliant when in DMX mode
- Electronic universal power supply 100-260 V AC, 50/60 Hz.
- SS/Brass lead screw type focusing mechanism for step less smooth zooming .
- 10 to 50 degree spot to flood beam spread
- Available with pole operated yoke.



OPTICAL SYSTEM

- Beam Angle : 10° to 50° steeples linear zoom
- Fresnel lens diameter : 200mm
- Lens Material: Annealed shock resistant borosilicate glass. (AUER German Made)

DMX CHART

- 1 Channel Mode : Dimmer, 0-100%

CONTROL

- On board Control with 5 No's High Precision Membrane switch with 7 segment display for easy to read status.
- USITT DMX512A (RDM Compatible) Control Protocol.
- 5 pin locking XLR Chassis mount DMX in & through connections
- 8 bit DMX control, extra soft dimming, for theatrical & Studio use.

PHYSICAL

- Rugged die-casted and extruded aluminium body
- Active Cooling system by Copper tube heatsink with Silent-running cooling fans ideal for TV studios & theatres
- Aluminum yoke
- Available in Manual and Pole operated system for Pan, Tilt and Focus.
- Epoxy polyester powder coated matt black finish (RAL – 9005) (Customizable as per requirements)
- IP Rating : IP20

200W – 3200K

WEIGHT & DIMENTION

Length	Width	Height	Weight
370 mm	250 mm	455 mm	7.6 Kg
1.21 ft	0.82 ft	1.49 ft	16.8 lbs

ACCESSORIES (Optional)

-  8 leaf Barndoor 360° Rotatable
-  4 leaf Barndoor 360° Rotatable
-  Snoot
-  Scrim & Filter frame
-  Clamps & Spuds
-  Power & DMX Cables


Photometric Data - Spot @ 10 Degrees - 3200K

Throw Distance	(m)	2	3	5	8	12
	(ft)	6.56	9.84	16.40	26.25	39.37
Beam Diameter	(m)	0.35	0.53	0.88	1.40	2.10
	(ft)	1.15	1.74	2.89	4.59	6.89
Illumination	(lux)	38270	17009	6123	2392	1063
	(fc)	3555	1580	569	222	99

Photometric Data - Flood @ 50 Degrees - 3200K

Throw Distance	(m)	1	2	3	4	5
	(ft)	3.28	6.56	9.84	13.12	16.41
Beam Diameter	(m)	0.93	1.87	2.80	3.73	4.67
	(ft)	3.06	6.12	9.18	12.25	15.31
Illumination	(lux)	14228	3557	1581	889	569
	(fc)	1332	330	147	83	53

SPECTRUM - 3200K



TM - 30

