

# LED FLOOD LIGHT

Canara High quality LED Flood light consist of LED's, having various beam angles support a variety of light distribution for different applications, including flood lighting and façade lighting.

## FEATURES

- Adopts original LED light source, high flux output, excellent consistency of light color ; constant current driver with PWM gray control installed inside.
- The brightness can be controlled by DMX512 signal, the adjustable range is 0-100%.
- With multiway rotate function of round support or "U" support available to meet the various occasions demands.
- Light body adopts high pressure die-casting aluminium, surface with electrostatic plastic coating.
- Lampshade adopts high strength toughened glass, resist the impact and friction.
- Available in optional beam angle lenses.
- Environmental friendly and free from UV, IR or Mercury.

## SPECIFICATIONS

LED power : 200W/250W/300W/350W/  
400W/450W/500W

Power Supply : AC100-240V, 50/60HZ/24V DC

Color Temperature : SINGLE COLOR/RGBW

CRI : > 80

Beam angle : Optional  
10°,15°,20°,30°,45°,60°,15x30°,10x60°

Protection rating : IP66/IP20

Control : Manual (On - Off) / DMX 512

LED lifetime : 50000 hours

Body : Die-cast aluminium casing

**Product Code : CAN LED SFL40  
CAN LED SFL60  
CAN LED SFL80  
CAN LED SFL100  
CAN LED SFL150**



## Applications :

Outdoor Landscape lighting such as hotels, shopping malls, buildings and bridges.

