

LED FLOOD LIGHT-D2

Canara High quality LED flood light consist of LED's, support a variety of light distribution for different applications, including flood lighting and façade lighting.

FEATURES

- Adopts original LED light source, high flux output, excellent consistency of light color ; constant current driver with PWM gray control installed inside.
- Light body adopts high pressure die-casting aluminium, surface with electrostatic plastic coating.
- Lampshade adopts high strength toughened glass, resist the impact and friction.
- Environmental friendly and free from UV, IR or Mercury.

SPECIFICATIONS

Power: 30W/50W/100W/150W/200W/250W/300W

Power Supply : AC100-277V, 50/60HZ

Color Temperature:3200K/4000K/5600K/6500K

Power Factor : > 0.95

Beam angle : 25°/45°/60°/90°/Asymmetric

Light Efficiency: 120lm/w

Protection rating : IP66,IK08

CRI: Ra>80

LED lifetime : 50000 hours

Body : Die-cast aluminium casing



Product Code : CAN LED SFL40

CAN LED SFL60

CAN LED SFL100

CAN LED SFL150

CAN LED SFL200

CAN LED SFL250

CAN LED SFL300

Applications :

Outdoor Landscape lighting such as hotels, shopping malls, buildings, bridges and sports Lighting etc.

CaNaRa
Lighting
GLOBAL ILLUMINATORS

LED FLOOD LIGHT-D2A

Canara High quality LED flood light consist of LED's, support a variety of light distribution for different applications, including flood lighting and façade lighting.

FEATURES

- Adopts original LED light source, high flux output, excellent consistency of light color ; constant current driver with PWM gray control installed inside.
- Light body adopts high pressure die-casting aluminium, surface with electrostatic plastic coating.
- Lampshade adopts high strength toughened glass, resist the impact and friction.
- Environmental friendly and free from UV, IR or Mercury.

SPECIFICATIONS

Power: 10W/20W/30W/50W/100W/150W/
200W/250W/300W

Power Supply : AC100-277V, 50/60HZ

Color Temperature:3200K/4000K/5600K/6500K

Power Factor : > 0.95

Beam angle : 120°

Light Efficiency: 110-120lm/w

Protection rating : IP66, IK08

CRI: Ra>80

LED lifetime : 50000 hours

Body : Die-cast aluminium casing



Product Code : CAN LED SFL40

CAN LED SFL60

CAN LED SFL100

CAN LED SFL150

CAN LED SFL200

CAN LED SFL250

CAN LED SFL300

Applications :

Outdoor Landscape lighting such as hotels, shopping malls, buildings, bridges and sports Lighting etc.

CaNaRa
Lighting
GLOBAL ILLUMINATORS

LED FLOOD LIGHT-D3

Canara High quality LED flood light consist of LED's, support a variety of light distribution for different applications, including flood lighting and façade lighting.

FEATURES

- Adopts original LED light source, high flux output, excellent consistency of light color ; constant current driver with PWM gray control installed inside.
- Light body adopts high pressure die-casting aluminium, surface with electrostatic plastic coating.
- Lampshade adopts high strength toughened glass, resist the impact and friction.
- Environmental friendly and free from UV, IR or Mercury.

SPECIFICATIONS

Power: 30W/50W/100W/150W/200W/250W/
300W/400W/500W

Power Supply : AC100-277V, 50/60HZ

Color Temperature:3200K/4000K/5600K/6500K

Power Factor : > 0.95

Beam angle : 30°/60°/90°/Asymmetric

Light Efficiency: 120lm/w

Protection rating : IP66,IK08

CRI: Ra>80

LED lifetime : 50000 hours

Body : Die-cast aluminium casing



Product Code : CAN LED SFL40
CAN LED SFL60
CAN LED SFL100
CAN LED SFL150
CAN LED SFL200
CAN LED SFL250
CAN LED SFL300

Applications :

Outdoor Landscape lighting such as hotels, shopping malls, buildings, bridges and sports Lighting etc.

CaNaRa
Lighting
GLOBAL ILLUMINATORS

LED FLOOD LIGHT-T1

Canara High quality LED flood light consist of LED's, support a variety of light distribution for different applications, including flood lighting and façade lighting.

FEATURES

- Adopts original LED light source, high flux output, excellent consistency of light color ; constant current driver with PWM gray control installed inside.
- Light body adopts high pressure die-casting aluminium, surface with electrostatic plastic coating.
- Lampshade adopts high strength toughened glass, resist the impact and friction.
- Environmental friendly and free from UV, IR or Mercury.

SPECIFICATIONS

Power: 50W/100W/150W/200W/250W/
300W/400W/500W/600W

Power Supply : AC100-277V, 50/60HZ

Color Temperature:3200K/4000K/5600K/6500K

Power Factor : > 0.95

Beam angle : 15°/30°/45°/60°/90°/Asymmetric

Light Efficiency: 140lm/w

Protection rating : IP66,IK08

CRI: Ra>80

LED lifetime : 50000 hours

Body : Die-cast aluminium casing



Product Code : CAN LED SFL40

CAN LED SFL60

CAN LED SFL100

CAN LED SFL150

CAN LED SFL200

CAN LED SFL250

CAN LED SFL300

CAN LED SFL350

CAN LED SFL500

CAN LED SFL600

Applications :

Outdoor Landscape lighting such as hotels, shopping malls, buildings, bridges and sports Lighting etc.



We innovate continuously, hence data & design given are subject to change without notice.

LED FLOOD LIGHT-HB1

Canara High quality LED linear high bay light consist of LED's, support a variety of light distribution for different applications, including flood lighting and façade lighting.

FEATURES

- Adopts original LED light source, high flux output, excellent consistency of light color ; constant current driver with PWM gray control installed inside.
- Light body adopts high pressure die-casting aluminium, surface with electrostatic plastic coating.
- Lampshade adopts high strength toughened glass, resist the impact and friction.
- Environmental friendly and free from UV, IR or Mercury.



Product Code : CAN LED SFL100
CAN LED SFL150
CAN LED SFL200
CAN LED SFL500

Applications :

Outdoor Landscape lighting such as hotels, shopping malls, buildings, bridges and sports Lighting etc.

SPECIFICATIONS

Power: 100W/150W/200W/400W

Power Supply : AC100-277V, 50/60HZ

Color Temperature:3000K/4000K/5700K

Power Factor : > 0.95

Beam angle : 120°/Asymmetric

Light Efficiency: 140lm/w

Protection rating : IP65

CRI: Ra>80

LED lifetime : 50000 hours

CaNaRa
Lighting
GLOBAL ILLUMINATORS