

250W – 5600K / 3200K

LED LENS PANEL LIGHT

Canara LED lens panel series LED lighting system has been specifically developed for film and video applications that demand extremely color-accurate, high quality light. Utilizing proprietary, state-of-the-art, daylight balanced LEDs, Canara LED Panel creates a high volume of broad spectrum white light, combined with an electronic flicker-free dimmable power supply unit to create a powerful yet economical LED lens light make it the perfect choice for TV studio, Production Studios, Film Recordings & Documentaries etc.,



MODEL : CLP-250D (5600K)
CLP-250T (3200K)

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

- Lamp : SMD LED ARRAY
- Color temperature (CCT) : 5600K or 3200K
- CRI : > 95, TLCI : > 95, R9 Value: > 95
- Color Quality Scale (CQS) : > 95
- Lamp life : L70 >50000 Hours @ 55°C

ELECTRICAL

- Flicker free universal auto-ranging electronic switch mode power supply 100~240 VAC Nominal, 50/60 Hz
- 0 to 100% 8 Bit Linear Dimming
- Power Factor ≥ 0.95 @ 230V 50Hz
- Max mains current drawn 1.13A @ 230V AC 50Hz
- Max LED current drawn 5.21A @ 48V DC
- Power supply cable: 2 meter 3 Core 1Sq mm FRLS grade PVC cable with IEC Plug

SPECIAL FEATURES

- Delivers the High-volume light output.
- Double accessories slot for inserting color Filters, Barndoor, Honeycomb screen and other accessories with lock retaining clip.
- Fully RDM Compliant when in DMX mode
- Non-glare, diffuser provides uniform, single source light.
- Efficient power and thermal management delivers low power consumption and enhanced reliability.
- Fanless design perfect for studio application
- All metal construction.
- No light spill to distract audiences or performers.
- Available with pole operated yoke.



OPTICAL SYSTEM

- Beam Angle : 30°
- Lens Material : PMMA Lens array
- Optical characters : Controlled light beam spread

DMX CHART

- 1 Channel Mode : Dimmer, 0-100%

CONTROL

- On board Control with 5 No's High Precision Membrane switch with 7 segment display for easy to read status.
- USITT DMX512A (RDM Compatible) Control Protocol.
- 5 pin locking XLR Chassis mount DMX in & through connections
- 8 bit DMX control, extra soft dimming, for theatrical & Studio use.

PHYSICAL

- Aluminium & MS laser cut body
- Passive Cooling system with large heatsink, no noise, perfect for TV studios & theatres
- Aluminum yoke
- Available in Manual and Pole operated system for Pan, Tilt and Focus.
- Epoxy polyester powder coated matt black finish (RAL – 9005) (Customizable as per requirements)
- IP Rating : IP20

250W – 5600K / 3200K


WEIGHT & DIMENTION

Length	Width	Height	Weight
665 mm	360 mm	125 mm	10.8 Kg
2.03 ft	1.08 ft	0.41 ft	23.8 lbs


ACCESSORIES (Optional)

-  4 leaf Barndoor or 8 Leaf Barndoor
-  Softbox
-  Honeycomb screen
-  Conical Diffuser
-  Clamps & Spuds
-  Power & DMX Cables


SPECTRUM - 3200K



SPECTRUM - 5600K



TM - 30 (3200K)



Photometric Data - @ 30 Degrees

Throw Distance	(m)	2	4	6	8	10
	(ft)	6.56	13.12	19.69	26.25	32.81
Beam Diameter	(m)	1.07	2.14	3.22	4.29	5.36
	(ft)	3.52	7.04	10.55	14.07	17.59
Illumination 5600K	(lux)	14260	3565	1584	891	570
	(fc)	1325	331	147	83	53
Illumination 3200K	(lux)	13700	3425	1522	856	548
	(fc)	1273	318	141	80	51

TM - 30 (5600K)

